

Hi Speed Dome Weatherproof Cameras & Accessories



WSPD-33WDR
Hi-Speed Dome PTZ
35x Zoom, WDR Camera

WSPD-26SP
Hi-Speed Dome PTZ
28x Zoom, Camera

WSPD-104F
Hi-Speed Dome PTZ
10x Zoom, Camera



RS485-LAN
3 Axis Joystick Keyboard
RS-485, PTZ Camera Controller



RSC-485
3 Axis Joystick Keyboard
RS-485, PTZ Camera Controller



High Quality for frequent and Heavy Dully Use

Cost Effective model

RS-232, RS-485 & Network connections

RS-485 connection

Support Multi Protocols
PELCO-D, PELCO-P, ...

Support Multi Protocols
PELCO-D, PELCO-P, ...

Baud Rate
1200, 2400, ... 19200, ...

Baud Rate
1200, 2400, ... 19200, ...

with LCS display,
Presel, Auto Scan, Auto Pan
Auto tour & Pattern Contr.
Auxiliary Function

with LCS display,
Presel, Auto Scan, Auto Pan

Interface RJ-45
IP Address/Port/Protocol
(Network model, only)

0

Power: 12VDC - 500mA
320 x 190 x 100mm
2.5kg

Power: 12VDC - 450mA
300 x 200 x 100mm
1.2kg

Color - 0.7Lux
BW - 0.02Lux
Sens-up - 0.007Lux

Color - 1Lux
BW - 0.1Lux

Color - 0.5Lux
BW - 0.1Lux

Color - 1Lux
BW - 0.1Lux

24VAC - max.2A
while Heater and Fan ON

24VAC - max.2A
while Heater and Fan ON

Weatherproof
IP-67, -40°C to 60°C

Weatherproof
IP-67, -40°C to 60°C

240(D)x374x318(H)mm
Brut Weight: 9 Kg

240(D)x374x318(H)mm
Brut Weight: 9 Kg

by RS-485 controller or DVR
Multiple Protocols: Pelco-D, ...

by RS-485 controller or DVR
Multiple Protocols: Pelco-D, ...

by RS-485
Multiple Protocols: Pelco-D, ...

8 Alarm Inputs
1 Alarm Output

8 Privacy Zones, Mirror, Cam ID
128 Presets Positions,
5 Auto Scans, 8 Auto Tours
5 Pattern, Digital Flip- Freeze
Ultra WDR, Image Stabilizer,
Built-in Heater & Cooler

8 Privacy Zones, Mirror, Cam ID
128 Presets Positions,
5 Auto Scans, 8 Auto Tours
5 Pattern, Digital Flip
Built-in Heater & Cooler

4 Privacy Zones, Mirror, Cam ID
Sens-up (x128), Motion Detect,
127 Presets Positions,
4 Pattern, 8 Swing & 8 Groups
Digital Flip

4 Privacy Zones, Mirror, Cam ID
Sens-up (x128), Motion Detect,
127 Presets Positions,
4 Pattern, 8 Swing & 8 Groups
Digital Flip


27x optical Zoom Lens
3.9~105 mm/F1.6
A Focus - DC Auto Iris
12VDC-250mA

1/4" SONY
Super HAD-EX View CCD
480 TVL, 12VDC-250mA
120x70x60mm - 480g



SDZ-270
27x Zoom Color Camera

Accessories
(optional)



Way of Control:

- By RS-485 PELCO-D, 2400bps
- By analogue controller: Zoom, Focus, Menu, Com
OSD (On Screen Display)