Hi Speed Dome Weatherproof Cameras & Accessories

	WSPD-35WDR Hi-Speed Dome PTZ 35x Zoom, WDR Camera	WSPD-26SP Hi-Speed Dome PTZ 26x Zoom, Camera	WSPD-10AF Hi-Speed Dome PTZ 10x Zoom, Camera
Image Sensor	1/4" SONY Super HAD-CCD	1/4" SONY Super HAD-Ex View CCD	1/3" SONY Interline Transfer CCD
Camera Module	HITACHI - Progressive scan **VK-S654E** Wide Dynamic Range	SONY **FCB-EX980SP**	SAMSUNG **SPD-1000**
Max. Resolution	Color - 540 TVL B/W - 580 TVL	Color - 520 TVL B/W - 570 TVL	Color - 520 TVL B/W - 570 TVL
Mechanism	PAN speed 360°/sec TILT speed 90°/sec	PAN speed 360°/sec TILT speed 90°/sec	PAN speed 360°/sec TILT speed 90°/sec
Lens	35x optical +12x Digital Zoom filter-changeable 3.4~119mm/F1.4 Auto Focus - DC Auto Iris	26x optical +12x Digital Zoom filter-changeable 3.5~91mm/F1.4 Auto Focus - DC Auto Iris	10x optical +10x Digital Zoom filter-changeable 3.8~38mm/F1.6 Auto Focus - DC Auto Iris
Min illumination (Sensitivity)	Color - 0.5Lux B/W - 0.1Lux	Color - 1Lux B/W - 0.1Lux	Color - 0.7Lux B/W - 0.02Lux Sens-up - 0.007Lux
Power Supply Max Consumption	24VAC - max.2A while Heather and Fan ON	24VAC - max.2A while Heather and Fan ON	DUAL-Power, Auto-detect 24VAC/12VDC, 500/850mA
Safety Level (IP)	Weatherproof IP-67, -40°C to 60°C	Weatherproof IP-67, -40°C to 60°C	Weatherproof IP-66, -25°C to 45°C
Dimension	240(D)x374x318(H)mm Brut Weight: 9 Kg	240(D)x374x318(H)mm Brut Weight: 9 Kg	168(D)x145mm Brut Weight: 3 Kg
Control	by RS-485 controller or DVR Multiple Protocols: Pelco-D...	by RS-485 controller or DVR Multiple Protocols: Pelco-D...	by RS-485 controller or DVR Multiple Protocols: Pelco-D...
Alarm (Input/Output)	by RS-485 Multiple Protocols: Pelco-D...	8 Alarm Inputs 1 Alarm Output	4 Alarm Inputs 1 Alarm Output
Other Features	8 Privacy Zones, Mirror, Cam ID 128 Presets Positions, 5 Auto Scans, 8 Auto Tours 5 Pattern, Digital Flip- Freeze Ultra WDR, Image Stabilizer... Built-in Heather & Cooler	8 Privacy Zones, Mirror, Cam ID 128 Presets Positions, 5 Auto Scans, 8 Auto Tours 5 Pattern, Digital Flip Built-in Heather & Cooler	4 Privacy Zones, Mirror, Cam ID Sens-up (x128), Motion Detect. 127 Presets Positions, 4 Pattern, 8 Swing & 8 Groups Digital Flip
Accessories (optional)	 **IB-SPD** Ceiling Bracket **PB-SPD** Pole Bracket	 **OCB-SPD** Corner Bracket	 DB-10AF Wall bracket

RS485-LAN 3 Axis Joystick Keyboard RS-485, PTZ Camera Controler	RSC-485 3 Axis Joystick Keyboard RS-485, PTZ Camera Controler
High Quality for frequent and Heavy Duty Use	Cost Effective model
RS-232, RS-485 & Network connections	RS-485 connection
Support Multy Protocols PELCO-D, PELCO-P, ...	Support Multy Protocols PELCO-D, PELCO-P, ...
Baud Rate 1200, 2400, ... 19200, ...	Baud Rate 1200, 2400, ... 19200, ...
with LCS display, Preset, Auto Scan, Auto Pan Auto Tour & Pattern Contr. Auxilary Function	with LCS display, Preset, Auto Scan, Auto Pan
Interface RJ-45 IP Address/Port/Protocol (Network model, only)	o
Power: 12VDC - 500mA	Power: 12VDC - 450mA
320 x 190 x 100mm 2.5Kg	300 x 200 x 100mm 1.2Kg

SDZ-270 27x Zoom Color Camera	
27x optical Zoom Lens 3.9~105 mm/F1.6 A. Focus -DC Auto Iris 12VDC-250mA	1/4" SONY Super HAD-Ex View CCD 480 TVL, 12VDC-250mA 120x70x60mm - 480g
Way of Control: - By RS-485 PELCO-D, 2400bps - By analogue controller: Zoom, Focus, Menu, Com OSD (On Screen Display)	